

**CLAIM AMENDMENTS**

1. (CANCELED)

2. (CANCELED)

3. (CANCELED)

4. (CANCELED)

5. (CANCELED)

6. (CANCELED)

7. (CANCELED)

8. (CANCELED)

9. (CANCELED)

10. (CURRENTLY AMENDED) A security apparatus comprising:

a section of material having two sides and a plurality of edges, including a top edge and a bottom edge;

~~The security apparatus of claim 2, further comprising a belt that tightens and reduces slack in said section of material;~~

an access means;

a plurality of coupling members that are each connected to said material; and

a plurality of attachment members selectively connected to said plurality of coupling members and selectively attached to a vertical or horizontal support structure;

wherein each of said plurality of attachment members is constructed for attachment to said vertical or horizontal support structure in a manner to permit fastening and unfastening of said attachment members from only one side of said material when attachment members are attached to said support structure and said section of material by said coupling members.

11. (PREVIOUSLY ADDED) The security apparatus of claim 10, wherein said belt is positioned at or near the bottom edge of said section of material.

12. (CANCELED)

13. (CANCELED)

14. (CANCELED)

15. (CANCELED)

16. (CANCELED)

17. (CANCELED)

18. (CANCELED).

19. (CANCELED)  
(CANCELED)

20. (CANCELED)

21. (CANCELED)

22. (CANCELED)

23. (CANCELED)

24. (CANCELED)

25. (CANCELED)

26. (CANCELED)

27. (CANCELED)

28. (CANCELED)

29. (CANCELED)

30. (CANCELED)

31. (CANCELED)

32. (CANCELED)

33. (CANCELED)

34. (CANCELED)

35. (CURRENTLY AMENDED) A security apparatus for guarding an interior area enclosed by three or more sides comprising:

a section of material;

a plurality of pairing members;

a plurality of fastening members for fastening said material to a support structure by said pairing members, at least one of said fastening members comprising a tightening member, said tightening member being configured for opening by hand without the use of a tool and comprising a The apparatus of claim 34, wherein said finger hold is circular finger hold for loosening and tightening said tightening member;

a means for entrance and exit;

wherein said pairing members are connected to said material; and wherein each of said plurality of fastening members are constructed for attachment to said structure in a manner to permit fastening and unfastening from only one side of said material when fastening members are attached to said structure with the section of material.

36. (CURRENTLY AMENDED) A security apparatus for guarding an interior area enclosed by three or more sides comprising:

a section of material;

a plurality of pairing members;

a plurality of fastening members for fastening said material to a support structure by said pairing members, at least one of said fastening members comprising a tightening member. ~~The apparatus of claim 32, wherein said tightening member is being configured for opening by use of a tool; and~~

a means for entrance and exit;

wherein said pairing members are connected to said material; and

wherein each of said plurality of fastening members are constructed for attachment to said structure in a manner to permit fastening and unfastening from only one side of said material when fastening members are attached to said structure with said section of material.

37. (PREVIOUSLY ADDED) The apparatus of claim 36, wherein said tool is a drill.

38. (PREVIOUSLY ADDED) The apparatus of claim 36, wherein said tool is an Allen wrench.

39. (CURRENTLY AMENDED) A security apparatus for guarding an interior area enclosed by three or more sides comprising:

a section of material;

a plurality of pairing members;

a plurality of fastening members for fastening said material to a support structure by said pairing members, at least one of said fastening members comprising a tightening member ~~The apparatus of claim 32, wherein one or more of said fastening members comprise~~ and a handle portion for holding said fastening members while attaching said fastening members to said structure; and

a means for entrance and exit;

wherein said pairing members are connected to said material; and

wherein each of said plurality of fastening members are constructed for attachment to said structure in a manner to permit fastening and unfastening from only one side of said material when fastening members are attached to said structure with the section of material.

40. (CURRENTLY AMENDED) A security apparatus for guarding an interior area enclosed by three or more sides comprising:

a section of material;

a plurality of pairing members;

a plurality of fastening members for fastening said material to a support structure

by said pairing members. The apparatus of claim 29, wherein one or more of at least one of said fastening members comprise comprising a hooked portion for grasping an edge of said structure; and

a means for entrance and exit;

wherein said pairing members are connected to said material; and

wherein each of said plurality of fastening members are constructed for attachment to said structure in a manner to permit fastening and unfastening from only one side of said material when fastening members are attached to said structure with the section of material.

41. (CURRENTLY AMENDED) A security apparatus for guarding an interior area enclosed by three or more sides comprising:

a section of material;

a plurality of pairing members;

a plurality of fastening members for fastening said material to a support structure by said pairing members. The apparatus of claim 29, wherein one or more of at least one of said fastening members comprise comprising a tightening member that works in conjunction with a hooked portion to hold an edge of said support structure; and

a means for entrance and exit;

wherein said pairing members are connected to said material; and

wherein each of said plurality of fastening members are constructed for attachment to said structure in a manner to permit fastening and unfastening from only one side of said material when fastening members are attached to said structure with the section of material.

42. (CANCELED)

43. (CURRENTLY AMENDED) A security apparatus for guarding an interior area enclosed by three or more sides comprising:

a section of material;

a plurality of pairing members;

a plurality of fastening members for fastening said material to a support structure by said pairing members;

a plurality of hanging members at a border of said section of material. The apparatus of claim 42, wherein said hanging members are being selectively attachable from said border of said section of material; and

a means for entrance and exit;

wherein said pairing members are connected to said material; and  
wherein each of said plurality of fastening members are constructed for  
attachment to said structure in a manner to permit fastening and unfastening from only one side  
of said material when fastening members are attached to said structure with the section of  
material.

44. (CANCELED)

45. (CURRENTLY AMENDED) A security apparatus for guarding an interior area  
enclosed by three or more sides comprising:

a section of material;

a plurality of pairing members;

a plurality of fastening members for fastening said material to a support structure  
by said pairing members;

a plurality of hanging members at a border of said section of material. ~~The~~  
~~apparatus of claim 42, wherein said hanging members comprise comprising~~ a projection having  
an end, said end adapted for removable connection to a lifting device; and

a means for entrance and exit;

wherein said pairing members are connected to said material; and

wherein each of said plurality of fastening members are constructed for  
attachment to said structure in a manner to permit fastening and unfastening from only one side  
of said material when fastening members are attached to said structure with said section of  
material.

46. (PREVIOUSLY ADDED) The apparatus of claim 45, wherein said lifting device  
comprises a pole.

47. (CURRENTLY AMENDED) A security apparatus for guarding an interior area  
enclosed by three or more sides comprising:

a section of material;

a plurality of pairing members ~~The apparatus of claim 29, wherein each of said~~  
~~pairing members comprise comprising~~ a grommet;

a plurality of fastening members for fastening said material to a support structure  
by said pairing members; and

a means for entrance and exit;

wherein said pairing members are connected to said material; and

wherein each of said plurality of fastening members are constructed for  
attachment to said structure in a manner to permit fastening and unfastening from only one side

of said material when fastening members are attached to said structure with the section of material.

48. (CURRENTLY AMENDED) A security apparatus for guarding an interior area enclosed by three or more sides comprising:

a section of material;

a plurality of pairing members ~~The apparatus of claim 29, wherein each of said pairing members comprise~~ comprising a ring;

a plurality of fastening members for fastening said material to a support structure by said pairing members; and

a means for entrance and exit;

wherein said pairing members are connected to said material; and

wherein each of said plurality of fastening members are constructed for attachment to said structure in a manner to permit fastening and unfastening from only one side of said material when fastening members are attached to said structure with the section of material.

49. (CANCELED)

50. (CURRENTLY AMENDED) A security apparatus for guarding an interior area enclosed by three or more sides comprising:

a section of material;

a plurality of pairing members ~~The apparatus of claim 29, wherein each of said pairing members comprise~~ comprising a rivet;

a plurality of fastening members for fastening said material to a support structure by said pairing members; and

a means for entrance and exit;

wherein said pairing members are connected to said material; and

wherein each of said plurality of fastening members are constructed for attachment to said structure in a manner to permit fastening and unfastening from only one side of said material when fastening members are attached to said structure with the section of material.

51. (CANCELED)

52. (CANCELED)

53. (CURRENTLY AMENDED) A security apparatus for guarding an interior area enclosed by three or more sides comprising:

a section of material;

a plurality of pairing members;  
a plurality of fastening members for fastening said material to a support structure  
by said pairing members; and  
a means for entrance and exit. ~~The apparatus of claim 29, wherein said entrance~~  
and exit means is being securable by a belt;  
wherein said pairing members are connected to said material; and  
wherein each of said plurality of fastening members are constructed for  
attachment to said structure in a manner to permit fastening and unfastening from only one side  
of said material when fastening members are attached to said structure with the section of  
material.

54. (CANCELED)